

IN THE SPECIFICATION:

Page 1, between lines 5 and 6 (underneath the title), insert –
BACKGROUND OF THE INVENTION –;

Page 4, between lines 14 and 15 insert – SUMMARY OF THE
INVENTION –;

Change Page 4, lines 18-19 to read as follows:

– This object is satisfied by a drive having the features of ~~claim 1~~ a
hydro machine whose injection volume is changeable, an adjustment device (10)
for changing injection volume of the hydro machine and having a first control valve
(5) which is in communication with the adjustment device (10) on the outlet side and
which is connected such that it effects a position of the adjustment device (10)
causing a low injection volume in a first position and a position of the adjustment
device (10) causing, compared thereto, a large injection volume in a second
position, wherein a control device, preferably a second control valve (3), is provided
on which an inlet pressure acts at the inlet side (300) and which is in communication
with a first control connection (50) of the first control valve (5) on the outlet side
(310), with a pressure loading of the first control connection (50) exerting a force
directed in the second position of the first control valve (5), and the control device,
preferably the second control valve (3), being connected such that it connects the
inlet side (300) to the first control connection (50) of the first control valve (5) in a
region of low performance requirements. Advantageous embodiments of the
invention result from the ~~dependent claims~~ disclosure herein.;

Page 7, between lines 24 and 25 insert – BRIEF DESCRIPTION OF
THE DRAWINGS –; and

Page 8, between lines 4 and 5 insert – DESCRIPTION OF THE
PREFERRED EMBODIMENTS –.